



ORASEAL

FLEXIBLE SEALING JOINT

NON-HARDENING

DEFINITION

Flexible, non-hardening sealing and locking paste (slackening).

ADVANTAGES

- Possesses excellent, long-lasting stability.
- Single-component, clean, easy-to-use and non-toxic. Protects against corrosion.
- Can be disassembled and cleaned easily. Can be used on all materials.
- Resists hot and cold water, sulphuric and phosphoric acid, soda, ammonia, ethylene glycol, thermal oil, etc.
- Compatible with KLINGER SIL C-4500 flange joints.

APPLICATION FIELDS

- Locking threads that must be moved frequently: idle screws, manometers, etc.
- Sealing mating surfaces, flanges and housings. Strengthening joints already in use.
- Can be used on paper gaskets, cork, and cardboard to make them stick.
- Hydraulic or pneumatic threaded seals.

TECHNICAL CHARACTERISTICS

Aspect	paste
Colour	green
Operating temperature	-50 to +300°C
Viscosity	8,000 cP
Maximum backlash advised	< 0.5 mm
Withstands pressure of	Up to 50 bars (depending on materials used).

INSTRUCTIONS FOR USE

Ready to use.
Application temperature: +5°C to +40°C.
Apply the adhesive evenly to clean and dry surfaces and fill in backlash entirely.
Commissioning can take place immediately after assembly.

Manufacturing site and registered office

Victoria Lub Pty Ltd
Factory 24/29 - 30 Kirkham Road West
Keysborough, VIC 3173
Tel. +03 9710 5373 – Fax. + 03 9701 5532
www.viclube.com.au

1/2

Victoria Lub. cannot know about every application for which the products are used nor their conditions of use. Victoria Lub. cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product for each specific case.

PACKAGING

100 g tube	Ref. 1342 T3	x 12
250 ml tin with brush	Ref. 1342 B4	x 6

ORAPI INFORMATION

Available in a thicker version: 343 – ORASEAL +.

Manufacturing site and registered office

Victoria Lub Pty Ltd
Factory 24/29 - 30 Kirkham Road West
Keysborough, VIC 3173
Tel. +03 9710 5373 – Fax. + 03 9701 5532
www.viclube.com.au

2/2

Victoria Lub. cannot know about every application for which the products are used nor their conditions of use. Victoria Lub. cannot be held responsible for the suitability of the products for a given use or a specific purpose. The information contained here can on no account be a substitute for the preliminary tests which are essential and which must be carried out in order to check the suitability of the product for each specific case.